

# DVL500-Compact - 300 m



Bottom-track from 0.3 to 175 m range; 300 m operational depth

The DVL500-Compact combines the compact design of the standard DVL1000 with the superior bottom-track range of the DVL500. It can fly higher in the water column and closer to the seabed than similar equipment, enabling small vehicles to do bigger jobs.

# DVL500-Compact - 300 m



## Highlights

- ✓ Bottom-track from 0.3-175 m range
- ✓ Per-ping and per-beam data quality estimates
- ✓ 300 m operational depth

## Applications

- ✓ Small vehicles requiring longer bottom track range
- ✓ Compact AUVs with high accuracy requirements
- ✓ Easy integration with leading inertial navigation systems (INS)

## Technical specifications

### —> Bottom velocity

Single ping std @ 3 m/s	0.5 cm/s
Long-term accuracy	±0.1% / ±0.1 cm/s
Minimum altitude	0.3 m
Maximum altitude	175 m
Velocity resolution	0.01 mm/s
Maximum ping rate	8 Hz max

### —> Water tracking

Minimum accuracy	0.3% of measured value ± 0.3 cm/s
Minimum range	4.0 m

### —> Current profiling

Minimum accuracy	0.3% of measured value ± 0.3 cm/s
Velocity resolution	0.1 cm/s
Interval	User-specified Nth ping
Maximum range	70 m
Blanking	0.5 m
Cell size	0.5-4.0 m
Max # cells	140

### —> Environmental

Operating temperature	-4 to +40 °C
Storage temperature	-20 to +60 °C
Vibration	IEC60068-2-64
EMC approval	IEC/EN 61000-6-2, 61000-6-3

### —> Mechanical

Depth rating	300 m
Weight	1.30 kg
Weight in water	0.15 kg
Height	158 mm
Diameter	ø 114 mm

### —> Hardware

Frequency of operation	500 kHz
Beam width	5.8°
Configuration	4-beam Janus array convex transducer, 25° beam angle
Internal memory	16 GB / 64 GB optional

# DVL500-Compact - 300 m



## → Hardware

Frequency of operation	500 kHz
Bandwidth	25% centered at transmit frequency

## → Interfaces

Serial (either serial or Ethernet)	Configurable RS232 or RS422 SubConn connector, 8-pin male
Ethernet	10/100 Mbits Auto MDI-X. TCP/IP, UDP/IP, HTTP protocols. Fixed IP / DHCP client / Auto IP address assignment. UPnP and Nortek proprietary instrument discovery over Ethernet. IEEE1588/PTP and NTP for absolute time stamping. Multiple simultaneous data format transmission possible.
Data formats	Nortek proprietary w/ 1 ms timestamp accuracy, NMEA0183, variants of PDX
Trigger	Internal 1, 2, 3, 4, 5, 6, 7 or 8 Hz or Trigger In. Trigger option through command (Ethernet or serial). External TTL or 485 lines: (configurable Rising/Falling/Edges)

## → Sensors

Pressure	0.1% FS /precision better than 0.002% of full scale per sample
Temperature	-4° to +40 °C ± 0.1 °C

## → Power

DC input	12-48 V
Maximum continuous current	1.5 A
Average power	3.0 W*

\* Power based on 1 Hz sampling and altitude with greatest transmit pulse.

## → Materials

Standard models	POM housing
-----------------	-------------